



AUTO SCRUBBER
APPROVED



AUTO SCRUBBER

STEP 1:

TANK MIX (4) OUNCES
CLEANER CONCENTRATE
INTO 15 GALLONS OF CLEAN
WATER. SCRUB THE CLEANING
SOLUTION WITH A NON-
ABRASIVE FLOOR PAD AT FULL
FLOW AND SQUEEGEE SET IN
THE FULL DOWN POSITION.

NOTE: 8 OUNCES FOR 30
GALLON TANKS

MOP & BUCKET

BUCKET MIX (1) OUNCE
CLEANER CONCENTRATE
TO (4) GALLONS CLEAN
WATER. PICK UP USING A
BUCKET OF CLEAN RINSE
WATER CHANGED
FREQUENTLY.

STEP 2:

CONTINUE TO APPLY AND EXTRACT
THE CLEANING SOLUTION WITH THE
SCRUBBER PADS ENGAGED. CLEAN
UNTIL THE SUPPLY TANK IS EMPTY
OR JOB IS COMPLETED . HEAVILY
SOILED FLOORS MAY REQUIRE
LONGER DWELL TIME AND/OR A
HIGHER CONCENTRATION.

STEP 3:

EMPTY BOTH THE SUPPLY AND
RETRIEVAL TANKS AND RINSE
WITH CLEAN WATER



SCAN FOR SDS

WARRANTY: RIO PRODUCTS ARE WARRANTED TO BE OF UNIFORM QUALITY, WITHIN MANUFACTURING TOLERANCES. THE MANUFACTURER HAS NO CONTROL OVER THE USE OF THIS PRODUCT, THEREFORE, NO WARRANTY, EXPRESSED OR IMPLIED, IS OR CAN BE MADE EITHER AS TO THE EFFECTS OR RESULTS OF SUCH USE. IN ANY CASE, THE MANUFACTURER'S OBLIGATIONS SHALL BE LIMITED TO REFUNDING THE PURCHASE PRICE OR REPLACING RIO PRODUCTS PROVEN DEFECTIVE. THE END USER SHALL BE RESPONSIBLE FOR DETERMINING PRODUCT'S SUITABILITY AND ASSUMES ALL RISKS AND LIABILITY.

